

# VFM HONDA



## TECHNICAL SPECIFICATIONS<sup>+</sup>

<b>BODY DIMENSIONS</b>	Length	2013 mm
	Width	786 mm
	Height	1115 mm
	Wheel Base	1347 mm
	Ground Clearance	160 mm
	Kerb Weight	Single Disc - 143 Kg, Double Disc - 144 Kg
	Seat Length	582 mm
	Seat Height	795 mm
	Fuel Tank Capacity	12 L
	<b>ENGINE</b>	Type
Displacement		162.71 cc
Max Engine Output		10.2 kW @ 8000 rpm
Max Torque		14.7 N-m @ 5500 rpm
Fuel System		PGM-FI
Bore x Stroke		57.300 X 63.096 mm
Compression Ratio		10.0:1
Starting Method		Self/Kick
<b>TRANSMISSION</b>	Clutch Type	Multiplate Wet Clutch
	No. of Gears	5 Gears
<b>TYRES &amp; BRAKES</b>	Tyre Size & Type (Front)	80/100-17 M/C 46P (Tubeless)
	Tyre Size & Type (Rear)	130/70-17 M/C 62P (Tubeless)
	Brake Type & Size (Front)	Disc - 276 mm (Single Channel ABS)
	Brake Type & Size (Rear)	Drum - 130 mm, Disc - 220 mm
<b>FRAME &amp; SUSPENSION</b>	Frame Type	Diamond Type
	Front Suspension	Telescopic
	Rear Suspension	Hydraulic, Monoshock
<b>ELECTRICALS</b>	Battery	12 V, 4.0 Ah
	Headlamp	LED

<sup>+</sup>The technical specifications and design of the vehicle may vary according to the requirements and conditions without any notice. Product shown in the picture may vary from actual product available in the market. Accessories shown in the picture are not part of standard equipment.

**KR PURAM**

93424 32151

**HENNUR**

91089 89818

**MAHADEVPURA**

96060 53051